

INSTALLATION INSTRUCTIONS:

MDI FIXED THROAT KNOCK-DOWN FRAME (KDF)

DATE: 04/15/14

INSTALLATION INSTRUCTIONS: MDI FIXED THROAT KNOCK-DOWN FRAME (KDF)

<p>1</p> <p>PREPARE ROUGH OPENING. TO DETERMINE THE ROUGH OPENING SIZE, ADD 2" TO THE NOMINAL DOOR WIDTH AND 1" TO THE NOMINAL DOOR HEIGHT. THIS IS FOR 2" FACET/IRMI FRAMES ONLY BY MDI. NOTE: LABELED OPENINGS REQUIRE A MINIMUM OF 1/2" OF DRYWALL ENGAGEMENT INTO FRAME THROAT.</p>	<p>2</p> <p>BEND SILL ANCHORS OUT OF FRAME AS SHOWN. THE SILL ANCHORS NEED TO BE BENT OUTWARD TO REST OUTSIDE THE STUD.</p>	<p>3</p> <p>INSTALL HEADER INTO POSITION APPROX. 1" FROM TOP AND IN THE CENTER OF THE ROUGH OPENING. ROTATE HEADER OVER DRYWALL AS SHOWN.</p>	<p>4</p> <p>INSTALL STRIKE JAMB BY SLIDING OVER WALL AT TOP AND ENGAGING CORNER REINFORCING INTO THE HEADER. PIVOT INTO PLACE. REPEAT WITH HINGE JAMB.</p>
<p>5</p> <p>REPEAT STEP # 4 WITH THE HINGE JAMB.</p>	<p>6</p> <p>TURN ADJUSTING (PRESSURE-FIT) SCREWS IN BOTH JAMBS COUNTERCLOCKWISE UNTIL ANCHOR IS RESTING AGAINST THE STUD. TIGHTEN MANUALLY. NOTE: DO NOT ATTEMPT TO TIGHTEN JUST ONE JAMB ANCHOR. BOTH ADJUSTING ANCHORS SHOULD BE TURNED EQUAL AMOUNTS ALTERNATELY.</p>	<p>7</p> <p>IF FEASIBLE, HANG DOOR NOW AND ADJUST FRAME ON WALL TO ALLOW PROPER DOOR/FRAME CLEARANCES OR PLUMB FRAME WITH CARPENTERS SQUARE AND/OR LEVEL. ADJUST FRAME TO HAVE TIGHT MITRES. NOTE: DO NOT ATTEMPT TO TIGHTEN JUST ONE JAMB ANCHOR. BOTH ADJUSTING ANCHORS SHOULD BE TURNED EQUAL AMOUNTS ALTERNATELY.</p>	<p>8</p> <p>CHECK DOOR OPENING DIMENSION AT BASE OF FRAME (MUST BE SAME DIMENSION AS BETWEEN JAMBS AT HEADER). STRAP ANCHOR @ BOTTOM: SECURE JAMBS WITH DRYWALL SCREWS (NOT FURNISHED) THROUGH STRAP ANCHOR AT BASE OF FRAME (BOTH SIDES). BE SURE TO ATTACH BOTH STRAP ANCHORS ON EACH JAMB (in 4 PLACES).</p> <p>NOTE: 1. MDI KD Frames must be installed with anchors as provided. Do not alter the frame in any way whatsoever. Any alteration or modification to the frame may void the fire rating or warranty. 2. Line drawings are for illustration purpose only. Actual product may vary from drawings. 3. Contact MDI for more details.</p>